















Overview

DT400 DIGITAL BATTERY TESTER

cod. 802605

Intelligent digital tester used to verify the charge status and start current capacity of 12V batteries (WET,GEL,AGM,PbCa). It is very compact, practical, easy to use and allows operations without disconnecting the battery from the vehicle; this is an enormous time saver during testing operations which become quick and easy to perform. The practical digital display and LED system provide instant viewing of the required information with high quality precision and efficient battery control. Moreover, the possibility to select the reference standard used by the battery manufacturers (EN,IEC,DIN,SAE,CA-MCA), each of which refers to the different ranges of start currents, is further confirmation of the exceptional versatility of this instrument.

Technical data

 CODE	CODE 802605	 CHARGING VOLTAGE	12 V	 BATTERY CAPACITY	20 - 200 Ah
 A_{MIN} / A_{MAX}	CURRENT RANGE 185/1125 - EN A	 A_{MIN} / A_{MAX}	CURRENT RANGE 130/790 - IEC A	 A_{MIN} / A_{MAX}	CURRENT RANGE 110/670 - DIN A
 A_{MIN} / A_{MAX}	CURRENT RANGE 200/1200 - SAE A	 A_{MIN} / A_{MAX}	CURRENT RANGE 240/1440 - CA(MCA) A	 T_c	OPERATING TEMPERATURE (MIN-MAX) 0 - 40 °C
 W / H / L	DIMENSIONS 7,8 - 2,2 - 14,5 cm	 kg	WEIGHT 0,18 kg	 BAR CODE	EAN CODE 800489779682 6