KOSHIN

Clear Water Pump

Diesel Engine

Powered by KOSHIN




SEV-50D

Outstanding Features

- KOSHIN NEW DIESEL ENGINE KD300
- Guaranteed 8M suction lift
- Suitable for mining, shipboard, fire-fighting and construction sites

	Model nan	ne	SEV-50D	SEV-80D	
Pump	Connection	Suction	50mm (2")	80mm (3")	
	dia	Discharge	50mm (2")	80mm (3")	
	Connection thread		Outer pipe thread BSP		
	Total head		32m (104 ft)	25m (82 ft)	
	Discharge volume		630L/min (166USG/min)	880L/min (232USG/min)	
	Max. suction head		8m (26 ft)		
Engine	Type		Forced air-cooled 4-stroke diesel engine		
	Model		KOSHIN KD300		
	Displacement		296cm3		
	Rated output		4.0kW (5.4 PS) / 3600rpm		
	Max. output		4.4kW (6.0 PS) / 3600rpm		
	Fuel		Diesel fuel		
	Fuel tank capacity		Tank size: 3.5L(0.92USG), Usage level: 3L(0.79USG)		
	Engine oil		CC or CD, Winter:5W-30, Other season:10W-30		
	Engine oil capacity		1.1L(0.29 USG)		
	Continuous operating time		Approx.2.3hrs	Approx.2.2hrs	
	Starting method		Recoil starter		
Applicable Liquids	Consistency		Clear water		
	Suspended solid percentage		•		
	Max. solids size				
	Temperature		5-45°C (41-113°F)		
Standard accessories			1 Strainer, 2 Coupling sets, 3 Hose bands, 1 Engine tool		
Net weight			46.1kg (101.6 lbs)	48.6kg (107.1lbs)	
Gross weight			50.8kg (111.9 lbs)	53.8kg (118.6lbs)	
Product dimensions L x W x H			600x520x550mm (24"x 21"x 22")		
Packing dimensions L x W x H			633x553x580mm (25"x 22"x 23")		



Self-priming performance may decrease due to atmospheric pressure or outside air temperature. If self-priming lift is not enough, add priming water to pump casing.



Robin Machineries and Equipment

P. O. Box 5229, Dubai – United Arab Emirates Tel: +971 4 221 7124 / 221 5841 Fax: +971 4 223 4493

Email: alawitra@emirates.net.ae Website: www.robinme.ae

^{*}For the purpose of improvement, specifications are subject to changes without notice,