

Submersible Pumps

PXJ / PKJ / PKG / PKJR Series



Grinder Pumps

- For sewage including small pieces of fabrics and organic waste etc.
- With high chrome grinder ring and impeller, objects can be ground and discharged without clogging
- Rust-resistant stainless body
- Impeller and pump housing are made from durable ductile cast iron



Check here for more information



PKG-750




Without sleeve



With sleeve




Grinder ring and impeller



SPECIFICATIONS

MODEL			PKG-750	PKG-1200	PKG-1500
PUMP	Connection dia	mm	32	32	32
		inch	1 1/4	1 1/4	1 1/4
	Total head	m	13	18	20.5
		ft	42.5	59.0	67.0
MOTOR	Discharge volume	L/min	175	180	180
		GPH	2770	2850	2850
	Voltage	V	220	220	220
	Frequency	Hz	50	50	50
Applicable liquids	Rated current	A	6.8	9.9	12.0
	Output	W	750	1200	1500
	Consumption	W	1400	1600	2000
	Consistency	Sandy and muddy water (suspended solids) *1			
Net weight (without cable)	Suspended solid percentage		10% *2		
	Max. solids size	mm	3	3	3
		inch	0.1	0.1	0.1
		kg	27.0	29.0	34.5
Standard accessories *3		lbs	59.5	63.9	76
	Hose coupling				

*1 Sandy and muddy water (suspended solids) are defined as debris "floating" within the water.
*2 If the suspended solid percentage is higher, premature wear and failure will occur.
To properly pump water with any debris, any solids must be in a suspension.
*3 Accessories may differ depending on model.



A Full Lineup with a Wide Range of Uses and Sizes.



ROBIN MACHINERY & EQUIPMENT
SOURCE OF TRUST

Robin Machinery & Equipment

Dubai, UAE | Tel: +97142217124

Email: inquiry@robinme.ae | Website: www.robinme.ae



Model		Dewatering Pumps				Vortex Pumps		Vortex Pumps			Grinder Pumps			Multi-purpose Pumps	
		PXJ-150	PXJ-250	PXJ-400	PXJ-750	PKJ-150	PKJ-250	PKJ-400	PKJ-750	PKJ-1500	PKG-750	PKG-1200	PKG-1500	PKJR-400	PKJR-750
Connection Dia	mm	15, 20, 25	40	50	50	32	40	50	50	80	32	32	32	50	50
Applicable Liquids		Clear water	Sewage			Sewage		Sewage			Sewage (Including organic waste, fibers etc.)			Sandy and muddy water	
Motor Output	W	150	250	400	750	150	250	400	750	1500	750	1200	1500	400	750
Total Head	m	6.0	8.5	10.5	14.0	6.0	6.0	7.0	11.0	11.0	13.0	18.0	20.5	11.0	17.0
Discharge Volume	L/min	95	190	195	325	150	225	245	340	680	175	180	180	215	330
Materials	Outer Pump Casing	Nylon	Stainless (SUS304)			Stainless (SUS304)		Stainless (SUS304)			Stainless (SUS304)			Die-casting alloy (ADC12)	
	Impeller	PC +GF			Ductile cast iron (FCD400)	PC +GF		PC +GF	Ductile cast iron (FCD400)		Ductile cast iron (FCD400)			Thermoplastic Polyurethane (TPU)	
	Pump Housing / Strainer	Resin	Stainless (SUS304)			ABS	Cast iron (FC200)	Cast iron (FC200)		Ductile cast iron (FCD400)				Cast iron (FC200)	